

# Ampacoll® Sleeves

For fast sealing of penetrations



- ▶ Waterproof, even when subject to movement and tension
- ▶ Non-aging
- ▶ Water repellent

## Application

After removing the first protective film, pull the seal over the tube and press into place at the level of the air seal. Now peel off the second part of the protective film and rub it down. The pad must be rubbed down firmly onto the substrate. It will bond immediately.

## Important Information

Films can release gases that affect the adhesion of the seal. OSB boards are sometimes coated with wax that contains paraffin, which can result in the seal being inadequately bonded. If in doubt, test the effectiveness of the bond.


## Technical details:

Working temperature range	above -5 °C
Temp. withstand range	-30 to +130 °C
Short-time exposure	up to +160 °C
Storage time	2 years
Storage conditions	cool and dry
Outdoor exposure time	3 months

# 10

Jahre Garantie\*  
Ans Garantie  
Anni Garanzia  
Years Warranty

\* Security is part of the system at Ampack. We cover the cost of removal and replacement, and consequential damage, as well as the replacement materials.

 ISO 9001:2008  
Swiss Research

## Ampacoll® Elektro 8

Diameter	8–11 mm	– Data cable
Adhesive area	150 x 150 mm	– Electrical cable
Sales unit	30 pieces	– Electrical ductwork
Pallet details	54 sales units	

## Ampacoll® Elektro 8 duo

Diameter	2 Stück à 8–11 mm	– Data cable
Adhesive area	150 x 150 mm	– Electrical cable
Sales unit	30 pieces	– For double feed-through
Pallet details	54 sales units	

## Ampacoll® Elektro 15

Diameter	15–22 mm	– Heating pipes
Adhesive area	150 x 150 mm	– Electrical ductwork
Sales unit	30 pieces	
Pallet details	54 sales units	

## Ampacoll® Elektro 25

Diameter	25–33 mm	– Solar pipes
Adhesive area	150 x 150 mm	– Water pipes
Sales unit	30 pieces	
Pallet details	54 sales units	

## Ampacoll® Install 42

Diameter	42–55 mm	– Waste water pipes
Adhesive area	230 x 230 mm	– Solar pipes
Sales unit	12 pieces	– Water pipes
Pallet details	25 sales units	

## Ampacoll® Install 100

Diameter	100–110 mm	– Waste water pipes
Adhesive area	320 x 320 mm	– Exhaust gas pipes
Sales unit	12 pieces	– Ventilation pipes
Pallet details	25 sales units	

## Ampacoll® Install 100 flex

Diameter	100–130 mm	– Waste water pipes
Adhesive area	320 x 320 mm	– Exhaust gas pipes
Sales unit	12 pieces	– Ventilation pipes
Pallet details	25 sales units	– Where a flexible feed-through is required

### Optimized for use with the following materials:

- ▶ Roof membranes
- ▶ Wall membranes
- ▶ Vapor checks and barriers
- ▶ Formwork strips
- ▶ Polythene films
- ▶ Soft fibreboards \*
- ▶ Medium-hard to hard fibreboards
- ▶ OSB boards
- ▶ Chipboard
- ▶ Gypsum plasterboard \*
- ▶ Gypsum fiberboard \*

\* use primer